

TS-2200



POSIFLEX
TS-2200

1D Omni-Directional Laser Table Scanner

Posiflex TS-2200 can read popular bar code types, and supports a wide range of scan patterns. The scanner also switches off automatically when standing by over the default period.

Key Features

- ▶ 1D Omni-directional laser scanner with a detachable cradle
- ▶ Aggressive first-pass scanning
- ▶ Powerful 7 directions scan field, 24 lines scan pattern
- ▶ Auto discriminates all standard 1D codes
- ▶ Programmable sleep mode, re-activated by pressing the sleep mode button
- ▶ Depth of Field : 300 mm
- ▶ Scan rate : 2400 scans per second for omnidirectional scanning
- ▶ Bottom mounting kit for fixing in the checkout
- ▶ Weight 450 g (Body)
- ▶ Interface support : RS232 or USB port



| Specification | TS-2200 |
|------------------------|---|
| Light Source | 650 nm Visible Laser Diode |
| Depth of Field | 300 mm (EAN 0.33 mm/13 mil, PCS 90%, Performance may be impacted by bar code quality and environmental conditions) |
| Scan Rate | 2400 scans per second |
| Scan pattern | 7 directions scan field, 24 lines scan pattern |
| Minimum Bar Width | 0.127 mm / 5 mils, PCS=40% |
| Print Contrast | PCS=40% |
| Indicators (LED) | Orange=Good Read |
| System Interfaces | Serial or USB port |
| Dimension | 152 x 152 x 91 mm |
| Weight | 450 g (Body only) |
| Cable Length | 3 M |
| Input Voltage | 12 VDC |
| Operating Current | 180 mA (2.2W max.) |
| Certifications | IEC 60825-1 (2007), EN-60950, CE, FCC, RoHS |
| Operating Temperature | 0°C to 40°C |
| Storage Temperature | -20°C ~ 60°C |
| Humidity | 5% to 90% RH (non-condensing) |
| Ambient Light Immunity | 0 - 6,400 Lux |
| Drop Durability | N/A |
| Bar Code Type | Auto discriminates all standard 1D codes. GS1 databar family, Omnidirectional, Stacked Omnidirectional, Expanded, Expanded Stacked, Truncated and Limited |

Design and Manufacturing In Taiwan by Posiflex Technology Inc.

** The product information and specifications are subject to change without prior notice.

2011 TS22Q2C1

