

Customer Line Display



PD-2800UE

- Standalone VFD Customer Line Display
- Adjustable pole height
- Green or Blue screen filter
- Two-line display with 20 characters per line
- Large character size for easy viewing : 9.03 mm x 5.25 mm
- 15° and 23° tilt angle adjustment
- Various command emulations selectable by DIP switch : ADM, Aedex, ESC/POS, Futaba, Noritake, UTC
- 12 international character sets support
- Interface : USB HID & USB Virtual COM selectable
- Dimension : 200mm (W) x 116 mm (D) x 265 mm ~ 395 mm (H);
Weight : 0.48 kg



PD-2702

- Embedded VFD Customer Line Display for POSIFLEX EP series terminal
- Two-line display with 20 characters per line
- Command emulations support : Aedex, ESC/POS, Futaba, Noritake, UTC
- Interface : Serial (Internal RS232 in EP series terminal)



POSIFLEX TECHNOLOGIES, INC.

6., Wu-Chuan Road, Wu-Ku, Taipei Hsien, Taiwan
TEL: +886.2.2299.1599 (Rep.) FAX: +886.2.2299.1819/1808
posiflex@posiflex.com.tw www.posiflex.com.tw



PD-201R

- Rear-top mounted LCD Customer Line Display for POSIFLEX DT series terminal
- Single-line display with 16 characters per line
- Command emulations support : PST (POSIFLEX proprietary command) & ESC/POS
- Interface : Serial



PD-320UE

- Standalone LCD Customer Line Display
- Adjustable pole height
- Blue character and yellow background
- Two-line display with 20 characters per line
- Large character size for easy viewing : 6.0 mm x 9.6 mm
- 15° and 23° tilt angle adjustment
- Command emulations support : PST (POSIFLEX proprietary command) & ESC/POS
- Interface : USB HID & USB Virtual COM selectable
- Dimension : 200 mm (W) x 116 mm (D) x 265 mm ~ 395 mm (H);
Weight : 0.48 kg