CITIZEN

Designed and built for performance
Stylish design and compact size
Thermal Transfer with standard Ethernet

CITIZEN CL-E321 CL-E331

Applications

- Durable Logistics
- Light manufacturing
- Asset labels
- Rating plates
- Garden tags and labels

Easier ribbon change

The CL-E321 uses full size, 300 meter ribbons with 1 inch cores and they are easily loaded into the 180° wide-opening case. The cleverly designed ribbon holders smoothly load the ribbon from any angle, with the arrows to show the winding direction

The distinctive blue-coloured media holder features a handle for simple label loading.

Stylish, Fast and Compact

The CL-E321's Compact, modern, functional design takes up very little desk space, is easy to use and is also perfectly at home in any location, from warehouses to hospitals. It also has a fast print speed of 8 inches-per-second. is quick to setup and to load with media.

Well connected

Featuring on board LAN, USB and Serial interfaces, the CL-E321 allows the printer to be operated remotely and settings adjusted thanks to its LinkServer™ management tool, which enables you to connect to the printer instantly via a web browser.

Easy operation

The CL-E321 is simple to use and intuitive, ensuring users waste no time when changing labels or adjusting settings.

CITIZEN SYSTEMS JAPAN CO,. LTD.

CITIZEN

On-board LAN, USB and Serial Interfaces

Specifications

Model	CL-E321	CL-E331
Printing technology	Thermal Transfer and Direct Thermal	
Resolution	203 dpi	300 dpi
Print Speed (maximum)	8 inches per second (200 mm/s)	6 inches per second (152mm/s)
Print Width (maximum)	4.1 inches (104 mm)	
Media Width (min to max)	0.94 inches to 4.65 inches (24 mm to 118 mm)	
Media Thickness (min to max)	63.5 μm – 190 μm, 0.0025 to 0.0075 inches	
Media Sensor	Adjustable gap & black mark sensors	
Media Length (min to max)	6.4 – 2540 mm, 0.25 – 100 inches depending on emulation and resolution	
Media Roll Size, Core Size	Up to 5 inches (125mm). Core 1 to 1.5 inches (25-38mm)	
Standard interfaces	10/100 Ethernet (LAN) with LinkServer™, USB 2.0, Serial RS232C	
Control Languages	Cross-Emulation™ - automatically switching between Zebra® ZPL-II® and Datamax®. CBI Basic Interpreter for programmers. EPL emulation coming soon.	
Case	Hi-Open™ plastic case with ClickClose™ Black and Pure White case colours	
Control Panel	Feed/Setting button and two LEDs (Power & Status)	
Memory configuration	16MB Flash (User area 4MB), 32MB SDRAM (User area 4MB)	
Drivers and software	Free-of-charge with printer, supporting Windows® 7, 8.1, 10, 2008R2, 2012, 2016, Linux and many others	
Size (W x D x H) and Weight	178 x 266 x 173 mm, 7.0 x 10.5 x 6.8 inches; 2.60 Kgs, 5.73 lbs (AC adapter, 0.36 Kgs, 0.79 lbs)	
Power consumption	110 to 240 VAC (90 to 264 VAC), 50 to 60 Hz, 60W typical power consumption when printing DOE VI / COC Tier 2 compliant (less than 0.15W no-load consumption)	
Printer, Head Warranty	1 Year for Printer; except Printhead, Main PCB and Power Adaptor	

All product names are trademarks of the respective manufactures. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availablity are subject to change without notice.Errors and omissions excluded. CITIZEN is a registered trademark of Citizen Watch Co., Ltd. Japan - V.1.0

Authorized National Distributor
AND
Authorized Service Centre for INDIA

CITIZEN CL-E321
CL-E331

LABEL

Features & Benefits

- Ethernet LAN, USB & Serial interfaces as standard
- Compact size and overall footprint to fit in small spaces
- One minute, tool-free maintenance. both head and platen can be replaced without tools
- Hi-Lift™ mechanism: full access for all operations including easy media / ribbon changing and sensor adjustment
- Adjustable media sensor as standard with label gap and black mark sensor
- Integral LinkServer™ web management enables easy operation and remote management of the printer
- Local pre sales and after sales service available

Barscan Systems & Ribbons Pvt Ltd

311, Apollo Chambers,
Mogra Village Road, Andheri (East),
Mumbai - 400 069.
Tel. : 022 - 40388100
website : www.barscansys.com
Email : barcode@barscansys.com